GRAVOPLY® 2

- Badges, Labels
- Interior Signage
- Micro-thin surface layer
- Perfect for small characters and detailed logos
- Low glare matt finish

Specifications

Surface	Matt
Profile engraving depth	0.1mm
Standard size (mm)	1220 x 610
Composition	ABS

Capabilities

Interior			Exterior
Shear			Saw
Silk screen			Hot stamp
Scratch resistant			Flexible
Break resistant			UV resistant
Min. temp.	0º C	60º C	Max, temp.

DID YOU KNOW?

We can custom manufacture your badges for you, so all you have to do is engrave. Double-sided: available on request in any of the standard colours. Minimum order of 10 sheets applies.



				2-ply		
	Surface colour	Core colour	0.8mm	1.5mm	2.4mm	
•	white	red	21857 -	21928 -	21989 -	
•	white	burgundy		21874		
•	white	blue	21841 -	21908 -	21973 -	
•	white	black	21850 -	21919 -	21982 -	
•	almond	burgundy		29709		
•	almond	black	21855 -	21926 -	-	
•	yellow	red	-	21913 -		
•	yellow	black	21863 -	21936 -	21995 •	
•	dark yellow	black	-	21925 -		
•	yellow	blue	21828 =	21896 =	-	
•	red	white	21851 -	21921 -	21983 •	
•	red	yellow	-	21910 -	-	
•	burgundy	white	-	21932 =	-	
•	brown	white	21858 =	21930 =		
•	chocolate brown	white	-	21876	-	
•	pine green	white	21865 =	21938 =	21997 =	
•	pine green	yellow	-	21916 =	-	
•	sky blue	white	21861 -	21934 =	21993 =	
•	sky blue	black	-	21895 =	-	
•	azure blue	white	21852 =	21923 =	-	
•	azure blue	yellow	-	21911 -	-	
•	air force blue	white	-	21907 =	-	
•	pewter	burgundy		29711		
•	grey	white	21856 =	21927 =	21988 =	
•	grey	black	-	21915 =	-	
•	pewter	navy		29712		
•	gunmetal	white	-	29713	-	
•	black	white	21849 =	21917 -	-	
•	black	yellow	21866 -	21940 -	-	
•	apple green	white		21905 -		
•	shadow blue	white		29714	-	

- carried in stock
- manufactured to order



Gravoply 2 products have a laserable foil cap, but their ABS core does not react well to lasering . When engraving with a laser, please take care to not engrave deep into the ABS core.



GRAVOPLY 2°

- Badges
- Interior Signage
- Gravoply 2 gloss has an extra durable, scratch resistant, glossy cap.
- Micro-thin surface layer
- Perfect for small characters and detailed logos
- Low glare, matt finish on wood, granite and tech patterns



Gravoply 2 Products have a laserable foil cap, but their ABS core does not react well to lasering. When engraving

with a laser, please take care to not engrave deep into the ABS core.

Specifications

Surface	Matt
Profile engraving depth	0.1mm
Standard size (mm)	1220 x 610
Composition	ABS

Capabilities

Interior			Exterior
Shear			Saw
Silk screen			Hot stamp
Scratch resistant			Flexible
Break resistant			UV resistant
Min. temp.	0º C	60º C	Max. temp.



The ultimate in scratch resistance!

or divopity		2-ply		
	Surface colour	Core colour	1.5mm	
•	white	black	23977 =	
•	white	red	23981 -	
•	yellow	black	23982 =	
•	red	white	23978 -	
•	emerald green	white	23983 -	
•	blue	white	23979 -	
•	grey	white	23980 -	
•	black	white	23976 =	

■ carried in stock

Gravoply® 2 Woods

1 /			2-ply	
	Surface colour	Core colour	1.5mm	
	satin light walnut	white	21885 -	
0	matt rosewood	white	21878 -	1
A CHARLE	matt american walnut	white	21879 -	9
	satin colonial walnut	white	21880 -	W.

■ carried in stock

Gravoply® 2 Granites

		2-ply	
Surface colour	Core colour	1.5mm	
green marble	almond	22026 -	
black	gray	22023 -	

■ carried in stock

Gravoply® 2 Tech Patterns

			2-ply	
	Surface colour	Core colour	1.5mm	
•	black pinstripe	white	22019 -	
•	silver pinstripe	black	22021 -	
•	black grid	white	22020 =	
	silver grid	black	22022 •	

■ carried in stock

✓ GRAVOGRAPH

